

MODELOS	IOVEN	HLB 860 P	HLB 840 P	HLB 860	HLB 840	HLB 830	HSB 635 P HSB 630 P	HSB 625 P HSB 620 P	HSB 645	HSB 635 HSB 630
Dimensiones interiores										
Alto (mm)	367	367	367	367	367	367	367	367	367	367
Ancho (mm)	475	475	475	475	475	475	475	475	475	475
Fondo (mm)	405	405	405	405	405	405	405	405	405	405
Capacidad neta/bruta (litros)	70 / 71	70 / 71	70 / 71	70 / 71	70 / 71	70 / 71	70 / 71	70 / 71	70 / 71	70 / 71
Conexión eléctrica										
Tensión (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Potencia nominal máxima (W)	3.198	3.552	3.552	3.215	3.215	2.615	3.552	3.552	3.215	2.615
Longitud cable de conexión (cm)	150+clavija	150+clavija	150	150+clavija	150	150	150	150	150	150
Consumos eléctricos										
Resistencia solera (W)	1.150	1.050	1.050	1.150	1.150	1.150	1.050	1.050	1.150	1.150
Resistencia grill: normal/maxigrill (W)	1.100/2.500	1.050/2.450	1.050/2.450	1.100/2.500	1.100/2.500	1.400	1.050/2.450	1.050/2.450	1.100/2.500	1.100/2.500
Resistencia bóveda + solera (W)	2.550	2.450	2.450	2.550	2.550	2.550	2.450	2.450	2.500	2.500
Resistencia turbo (W)	2.000	2.000	2.000	2.000	2.000	-	-	-	2.000	-
Turbina multifunción (W)	22	25	25	22	22	22	25	25	22	22
Iluminación interior (W)	4 x 2 LED	25	25	25	25	25	25	25	25	25
Motor refrigeración (W)	18	30	30	18	18	18	30	30	18	18
Sistemas de seguridad										
Desconexión autom. en puerta	✓	✓	✓	✓	-	-	✓	✓	-	-
Bloqueo de seguridad del panel	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Protector de grill	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Anti-vuelco de parrillas/bandejas	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Nº de cristales en puerta	3	4	4	3	2	2	4	3	2	2
Clase de eficiencia energética										
Eficiencia energética (¹)	A ⁺	A ⁺	A ⁺	A ⁺	A ⁺	A ⁺	A ⁺	A ⁺	A ⁺	A ⁺

MODELOS	HSB 615 HSB 610	HBB 605	HBB 535 HBB 510	HBB 435 HBB 490	ADVAND COMBO 45.15	ADVAND HL 940	EBON HS 900	COUNTRY STYLE HR 750	COUNTRY STYLE HR 550
Dimensiones interiores									
Alto (mm)	367	367	367	367	215 / 117	318	318	315	315
Ancho (mm)	475	475	475	465	452 / 418	639	639	466	466
Fondo (mm)	405	405	441	441	395 / 368	380	380	390	390
Capacidad neta/bruta (litros)	70 / 71	70 / 71	76 / 77	72 / 75	38-18 / 48-31 77 / 91	77 / 91	77 / 91	57 / 65	57 / 65
Conexión eléctrica									
Tensión (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Potencia nominal máxima (W)	2.615	2.615	2.593	2.593	2505 / 3643	3.553	2.848	2.693	2.623
Longitud cable de conexión (cm)	150	150	150	150	200	190+clavija	110	110	110
Consumos eléctricos									
Resistencia solera (W)	1.150	1.150	1.150	1.150	1050 / 1800	1.055	1.055	1.150	1.150
Resistencia grill: normal/maxigrill (W)	1.400	1.400	1.400	1.400	1400 / 1800	1.700/2.750	1.700/2.750	1.500/2.600	1.400
Resistencia bóveda + solera (W)	2.550	2.550	2.550	2.550	2450 / 3600	2.105	2.105	2.250	2.550
Resistencia turbo (W)	-	-	-	-	- / -	2.400	-	2.000	-
Turbina multifunción (W)	22	22	-	-	30 / -	30	30	30	30
Iluminación interior (W)	25	25	25	25	25 / 25	25 + 25	25 + 25	25	25
Motor refrigeración (W)	18	18	18	18	18 / -	18	18	18	18
Sistemas de seguridad									
Desconexión autom. en puerta	-	-	-	-	- / ✓	✓	✓	✓	-
Bloqueo de seguridad del panel	-	-	-	-	✓ / ✓	✓	-	-	-
Protector de grill	✓	✓	✓	✓	✓ / -	✓	✓	✓	✓
Anti-vuelco de parrillas/bandejas	✓	✓	✓	✓	✓ / ✓	✓	✓	✓	✓
Nº de cristales en puerta	2	2	2	2	2 / 2	3	3	2	2
Clase de eficiencia energética									
Eficiencia energética (¹)	A	A	A	A	A / -	A	A	A	A